(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property **Organization**

International Bureau



(43) International Publication Date 14 October 2004 (14.10.2004)

PCT

(10) International Publication Number WO 2004/088166 A1

(51) International Patent Classification7:

F16H 1/32

(21) International Application Number:

PCT/GB2004/001477

(22) International Filing Date:

5 April 2004 (05.04.2004)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

0307886.2 0321721.3

GB 4 April 2003 (04.04.2003) 16 September 2003 (16.09.2003) GB

(71) Applicant and

(72) Inventor: HAMMERBECK, John, P., R. [GB/GB]; Rawlings House, 2a Milner Street, London SW3 2PU


(74) Agents: ROBERTS, Gwilym, Vaughan et al.; Kilburn & Strode, 20 Red Lion Street, London WC1R 4PJ (GB).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: RATIO CHANGING METHOD AND APPARATUS



(57) Abstract: A ratio changing method and apparatus includes, in a hypocycle arrangement, an input drive wheel (2), an output drive wheel (3) and a transfer ring (1). The input drive wheel (2) drives around the exterior of the transfer ring (1). The transfer ring (1) is constrained against rotation about its own axis but oscillates about the outward drive wheel (3), in parting rotation to the output drive wheel (3) as a result a simple and effective ratio changing apparatus is provided.

WO 2004/088166 A1



Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.